

switching controlling counting

www.hugo-mueller.de



Product overview

ELAPSED TIME COUNTERS



BW 40.18



TRIM



MASK



BW 30.18



BW 70.18

CODE	DESCRIPTION	VOLTAGE
BG 40.17	48X48	12-48VDC
BW 40.18		24VAC 60Hz
BW 40.18		110/115VAC 60Hz
BW 40.18		230VAC 60Hz
BW 40.18		400/420VAC 60Hz

CODE	DESCRIPTION	VOLTAGE
BW 40.18	48X48	24VAC 50Hz
BW 40.18		110/115VAC 50Hz
BW 40.18		230VAC 50Hz
BW 40.18		400/420VAC 50Hz

CODE	DESCRIPTION	VOLTAGE
BW 30.18	53X24	230VAC 50Hz

ACCESSORIES	DIMENSIONS
Trim	55X55
Mask	72X72

CODE	DESCRIPTION	VOLTAGE
BW 70.18	Din-Rail Mounting 17,5mm	230VAC 50Hz

Save Time

Elapsed time counters

	müller BG 30.18 BW 30.18	DC / Front 53 x 28 mm AC / Front 53 x 28 mm	- Switchboard panel - Integral locking spring - With universal connections - Mounting aperture: 50 x 25 mm - With operation indicator
	müller BG 40.17 BW 40.18 BG 40.27 BW 40.28 BG 40.37 BW 40.38	DC / Front 48 x 48 mm AC / Front 48 x 48 mm DC / Front 55 x 55 mm AC / Front 55 x 55 mm DC / Front 72 x 72 mm AC / Front 72 x 72 mm	- Switchboard panel - With retaining clip - With universal connections - Mounting aperture square: 45x45mm / circle: 50,5mm - With operation indicator
	müller BG 70.18 BW 70.18	DC AC	- DIN-rail mounting 17,5 mm - No terminal cover - Screw terminals (pull-up type) - Touch proof connections - With operation indicator
	müller BG 70.29 BW 70.29 BG 70.89 BW 70.89	DC / without terminal cover AC / without terminal cover DC / with terminal cover AC / with terminal cover	- DIN-rail mounting 35 mm - With or without terminal cover - Screw terminals (pull-up type) - Touch proof connections - With operation indicator

Count down timers / Relays

	müller TC 14.21 TC 24.21	9:59:59 hh:mm:ss 99:59:59 hh:mm:ss	- Timer - Panel mounting - Front 48 x 48 mm 1 change-over relay - Repeatability accuracy 100% - Inputs for START / STOP
	müller MR 28.10 pro	999:59:59:59 hhh:mm:ss:1/10s	- Digital multifunctional relay - DIN-rail mounting 35 mm 1 channel (CO) 20 functions - External input
	müller EA 36.22 pro4	Universal controller 2 channels 2 inputs Remote-controllable	- Time switch week / astro - Blind controller - Flush-mounted fitting 100 memory locations - Programmable and controllable via app - Timer function with advance warning

Accessories

	müller DK pro	Data-key	- Data-key for Programming Package PP 50.00 pro - Accessory for pro-devices and SC 98.40 knx - Convenient programming of switching times on the PC
	müller PP 50.00 pro	Programming Package USB	- Programming Package Save'n carry - Accessory for pro-devices and SC 98.40 knx - Convenient programming of switching times on the PC - Data download from key to PC, modification of data and upload to key - Switching programs can be archived on the PC
	müller FU 20.00 pro FU 30.00 pro	DCF-time GPS-time	- Radio receiver - FU 20.00 pro: 2-wire-connection - FU 30.00 pro: 3-wire-connection - Accessory for time switches and master clocks - Time and date are automatically transferred to the time switch
	Trim 55x55 for Bx 40 / TC x4 / SC 24.10 pro Order number 190.003		Self-adhesive seal for Bx 40 / TC x4 / SC 24.10 pro Order number 101.001
	Mask 72x72 for Bx 40 / TC x4 / SC 24.10 pro Order number 190.004		IP54-seal for Bx 40 / TC x4 / SC 24.10 pro Order number 101.003
	Mask Ø 72 (installation Ø 60) for Bx 40 / TC x4 / SC 24.10 pro Order number 190.008		Retaining clip for Bx 40 / TC x4 / SC 24.10 pro Order number 715.003
	Terminal Cover for Bx 29 Order number 003.008 (black) Order number 003.010 (white)		Retaining clip for Bx 30 Order number 715.005

Analogue time switches

	müller VS 10.18 VS 14.18	paladin 111 120 114 120	Day without reserve Day with reserve	- Daily program - DIN-rail mounting 17,5 mm - Captive setting keys - Manual override switch - Permanent ON / Permanent OFF / AUTO
	müller VS 20.18 VS 24.18	paladin 151 220 154 220	Day without reserve Day with reserve	- Daily program - DIN-rail mounting 35 mm - Captive setting keys - Manual override switch - Permanent ON / Permanent OFF / AUTO
	müller VS 30.18 VS 34.18	paladin 131 120 134 120	Day without reserve Day with reserve	- Daily program - DIN-rail mounting 52,5 mm - Wall mounting - Captive setting keys - Manual override switch - Permanent ON / Permanent OFF / AUTO
	müller FS 60.18 FS 64.18 FS 60.38 FS 64.38	paladin 161 120 164 120 161 420 164 420	Day without reserve Day with reserve Week without reserve Week with reserve	- Daily / Weekly program - Wall mounting - Switchboard panel - Captive setting keys - Manual override switch - Permanent ON / Permanent OFF / AUTO

Digital time switches year

	müller SC 28.19 pro	1 channel version	- Daily, weekly and yearly program - DIN-rail mounting 35 mm 300 memory locations - Programmable via PC / Data-key - DCF / GPS function
	müller SC 98.10 pro4 SC 98.20 pro4 SC 98.30 pro4 SC 98.40 pro4	1 channel version 2 channel version 3 channel version 4 channel version	- Daily, weekly or astro program / Yearly program - DIN-rail mounting 70 mm 300 memory locations / Programmable via app - DCF / GPS function - Exchangeable battery

Masterclocks

	müller SC 58.07 pro	1 slaveclock line	- Master clock - DCF / GPS function - Approx. 5 slave clocks - Security by PIN-code
	müller SC 58.08 pro	1 slaveclock line	- Master clock - Suitable for church clocks - DCF / GPS function - Security by PIN-code
	müller SC 58.17 pro	1 slaveclock line 1 channel	- Master clock and digital time switch week 300 memory locations - DCF / GPS function - Approx. 20 slave clocks - Security by PIN-code
	müller SC 98.47 pro	1 slaveclock line 4 channels	- Master clock and digital time switch year 300 memory locations - DCF / GPS function - Approx. 40 slave clocks - Security by PIN-code
	müller SC 93.47 pro	1 slaveclock line 4 channels	- Master clock and digital time switch year 19"-housing 300 memory locations - DCF / GPS function - Approx. 200 slave clocks - Security by PIN-code
	müller SC 95.47 pro	1 slaveclock line 4 channels	- Master clock and digital time switch year 19"-housing 300 memory locations - DCF / GPS function - Approx. 200 slave clocks - Security by PIN-code

Illuminate

Staircase lighting timers

	paladin 284 210	Without advance warning	- Staircase lighting timer - Electronic - DIN-rail mounting 17,5 mm 3- or 4-conductor rising mains - Zero-cross switching - Resettable
	284 250	With advance warning	

Twilight switches

	paladin 972 413 easy	1 channel version	- Digital twilight switch - With daily program - DIN-rail mounting 35 mm - Programmable via app - Ideal for modern lamps (LED) - Exchangeable battery
	paladin 922 000	1 channel version	- Analogue twilight switch - Wall mounting - Ideal for modern lamps (LED)
	paladin 923 500	1 channel version sensor for wall mounting	- Analogue twilight switch - DIN-rail mounting 17,5 mm - Zero-cross switching - Ideal for modern lamps (LED)



Dimmers

	paladin 873 010 rlc	for RLC loads	- RLC dimmer - Flush-mounted fitting - Dimensions: 46 x 42 x 13 mm - Load 15 - 400 W - Memory function - With litz wires
	paladin 873 030 led	for LED loads	- LED dimmer - Flush-mounted fitting - Dimensions: 46 x 42 x 13 mm - Load 4 - 100 W / 350 W - Memory function - With litz wires
	paladin 873 031 led	for LED loads without neutral wire	- LED dimmer without N-wire - Flush-mounted fitting - Dimensions: 46 x 42 x 13 mm - Load 4 - 80 W / 200 W - Memory function - With litz wires
	paladin 873 040 led	for LED-strips	- LED-strips dimmer - Flush-mounted fitting - Dimensions: 46 x 42 x 13 mm - LED-strips 8 A - Memory function - With litz wires
	paladin 872 110 led	for LED loads	- LED dimmer / Universal dimmer - DIN-rail mounting 17,5 mm - LED Load 4 - 80 VA - Memory function - Master-slave-function
	paladin 879 410 led	for dimmable LEDs	- TRIAC dimmer for LED lamps - DIN-rail mounting 87,5 mm - Dimmable LEDs 4 - 1.200 W - Memory function - Master-slave-function

Astro dimmers

	paladin 872 413 pro4	LED dimmer	- LED dimmer - Astro function - DIN-rail mounting 35 mm - LED loads 4 - 150 W / trailing edge dimming 100 memory locations / Programmable via app
---	--	-------------------	---

Smart Bluetooth dimmers

	müller EA 26.11 pro4	LED dimmer mini	- LED-dimmer with astro function - Flush-mounted fitting - LED-loads 4 - 150 W / trailing edge dimming - Remote control via Bluetooth mesh / gateway - Programmable and controllable via App
	müller EA 27.11 pro4	LED-strip dimmer mini	- LED-dimmer with astro function - Flush-mounted fitting - LED strips (12-24 V DC) 4 A / pulse width modulation - Remote control via Bluetooth mesh / gateway - Programmable and controllable via App
	müller EA 66.11 pro4	LED dimmer	- LED-dimmer with astro function - Flush-mounted fitting - LED-Last 4 - 150 W / trailing edge dimming - Remote control via Bluetooth mesh / gateway - Programmable and controllable via App
	müller EA 76.10 pro4	Touch LED dimmer	- LED-dimmer with astro function - Flush-mounted fitting - LED-Last 4 - 150 W / trailing edge dimming - Remote control via Bluetooth mesh / gateway - Programmable and controllable via App

Feel Well

0-10V sensors

	müller TS 30.00 pro	Room temperature sensor	■ Temperature sensor ■ Wall mounting / modern and planar design / 80 x 80 mm ■ Control output (0 - 10 V)
	müller GS 30.00 pro	Room temperature sensor & rel. humidity sensor	■ Temperature, humidity and atmospheric pressure sensor ■ Wall mounting / modern and planar design / 80 x 80 mm ■ 2 control outputs (0 - 10 V)
	müller GS 40.00 pro	CO ₂ -air quality sensor & room climate sensor	■ CO₂, temperature, humidity and atmospheric pressure sensor ■ Wall mounting / modern and planar design / 80 x 80 mm ■ 3 control outputs (0 - 10 V)

Modbus sensors

	müller TS 30.00 mod	Room temperature sensor	■ Temperature sensor ■ Wall mounting / modern and planar design / 80 x 80 mm ■ Modbus ASCII and RTU
	müller GS 30.00 mod	Room temperature sensor & rel. humidity sensor	■ Temperature, humidity and atmospheric pressure sensor ■ Wall mounting / modern and planar design / 80 x 80 mm ■ Modbus ASCII and RTU
	müller GS 40.00 mod	CO ₂ -air quality sensor & room climate sensor	■ CO₂, temperature, humidity and atmospheric pressure sensor ■ Wall mounting / modern and planar design / 80 x 80 mm ■ Modbus ASCII und RTU

Air quality sensors / CO₂-monitor

	müller GS 42.00 pro	CO ₂ -monitor with power supply for flush-mounting	■ Air quality sensor / CO₂-monitor ■ Wall mounting / modern and planar design / 80 x 80 mm ■ CO₂ sensor ■ Maintenance-free through self-calibration ■ Mute function ■ 3 open collector outputs
	GS 42.01 pro	CO ₂ -monitor with power supply with Europlug / wall plug incl. back part 2	

Digital time switches astro


	müller SC 08.13 pro	paladin 172 113 pro	1 channel version	- Astro program - Daily and weekly program - DIN-rail mounting 17,5 mm 60 memory locations / PC-programmable - Removable programming module
	müller SC 18.13 easy	paladin 170 413 easy	1 channel version	- Astro-daily-program - DIN-rail mounting 35 mm 4 memory locations / Programmable via app - Ideal for modern lamps (LED) - Exchangeable battery
	müller SC 18.14 easy SC 18.24 easy	paladin 170 414 easy 170 424 easy	1 channel version 2 channel version	- Astro program - Daily and weekly program - DIN-rail mounting 35 mm 56 memory locations / Programmable via app - Ideal for modern lamps (LED) - Exchangeable battery
	müller SC 28.13 pro4 SC 28.23 pro4	paladin 172 413 pro4 172 423 pro4	1 channel version 2 channel version	- Astro program - Daily and weekly program - DIN-rail mounting 35 mm 100 memory locations / Programmable via app - Ideal for modern lamps (LED) - Exchangeable battery
		paladin 173 113 easy	1 channel version	- Astro program - Daily and weekly program - Flush-mounted fitting 56 memory locations / Programmable via app - Ideal for modern lamps (LED)
	müller EA 36.22 pro4		Universal controller 2 channels 2 inputs Remote-controllable	- Time switch week / astro - Blind controller - Flush-mounted fitting 100 memory locations - Programmable and controllable via app - Timer function with advance warning

Blind controllers


	müller EA 36.22 pro4	Universal controller 2 channels 2 inputs Remote-controllable	- Time switch week / astro - Blind controller - Flush-mounted fitting 100 memory locations - Programmable and controllable via app - Timer function with advance warning
---	--------------------------------	---	---

smart home

mi.puck switches

	müller EA 16.11 pro4	Multifunctional device 1 channel 1 input mini	- Time switch week / astro - Clock thermostat / hygrosat (with LS 20.00 pro4) - Flush-mounted fitting - Remote control via Bluetooth mesh / gateway
	müller EA 46.13 pro4	Multifunctional device 1 channels 1 inputs 1 temperature sensor (incl. TF 16)	- Time switch week / astro - Clock thermostat (with TF 06 (floor) / TF 16 (room)) - Clock thermostat / hygrosat (with LS 20.00 pro4) 16 A switching capacity - Flush-mounted fitting - Remote control via Bluetooth mesh / gateway
	müller EA 46.22 pro4	Multifunctional device 2 channels 2 inputs	- Time switch week / astro - Blind controller - Clock thermostat / hygrosat (with LS 20.00 pro4) - Flush-mounted fitting - Remote control via Bluetooth mesh / gateway

mi.puck dimmers

	müller EA 26.11 pro4	LED-dimmer mini	- LED-dimmer with astro function - Flush-mounted fitting - LED loads 4 - 150 W / trailing edge dimming - Remote control via Bluetooth mesh / gateway
	müller EA 27.11 pro4	LED-strip dimmer mini	- LED-dimmer with astro function - Flush-mounted fitting - LED strips (12 - 24 V DC) 4 A / pulse width modulation - Remote control via Bluetooth mesh / gateway
	müller EA 66.11 pro4	LED-dimmer	- LED-dimmer with astro function - Flush-mounted fitting - LED loads 4 - 150 W / trailing edge dimming - Remote control via Bluetooth mesh / gateway
	müller EA 76.10 pro4	Touch LED-dimmer	- Touch LED-dimmer with astro function - Flush-mounted fitting / fits into 55 x 55 mm switch design - LED loads 4 - 150 W / trailing edge dimming - Remote control via Bluetooth mesh / gateway

mi.puck sensor

	müller LS 20.00 pro4	Multisensor	- Light / brightness, temperature and rel. humidity sensor - Suitable for: EA 16.11 pro4, EA 46.13 pro4 und EA 46.22 pro4 - Wall mounting / fits into 55 x 55 mm switch design / outdoor installation - Compact housing
---	--------------------------------	-------------	--

mi.puck accessories

	müller TF 06 TF 16	sensor / probe 4 m sensor / probe 20 cm	- External temperature sensor - Measuring range: -15...+70°C - Cable length: 4 m / 20 cm - Suitable for: EA 46.13 pro4
	müller 200.001	Mounting plate for wall box	Suitable for LS 20.00 pro4
	200.002	Mounting angle for outdoor installation	- Suitable for LS 20.00 pro4 - Wall mounting
	mi.puck App	Free download	- App to control the mi.puck devices remotely - Creating a network with Bluetooth mesh - Integrated gateway function

KNX

KNX Audio Interface

	müller AS 10.00 knx	Buzzer	- Buzzer - Wall mounting / fits into 55 x 55 mm switch design / outdoor installation - Compact housing 3 volume levels - Adjustable sequence
	müller AS 26.01 knx AS 26.11 knx	Chime interface without loudspeaker Chime interface with loudspeaker (LA 06.10)	- Chime interface - Flush-mounted fitting 12 melodies selectable - Adjustable sound level - External loudspeaker 1 binary input
	müller AS 36.03 knx AS 36.13 knx	Audio interface without loudspeaker Audio interface with loudspeaker (LA 06.10)	- Audio interface - Flush-mounted fitting 6 individual MP3-files, 12 pre-defined melodies - Adjustable sound level - External loudspeaker 3 binary inputs

KNX Room temperature controllers

	müller TS 10.00 knx	Room temperature controller	- Room temperature controller - Wall mounting / fits into 55 x 55 mm switch design / outdoor installation - Compact housing - Temperature sensor
	müller TS 30.11 knx TS 31.11 knx	Room temperature controller Room temperature controller with manual set-point temperature adjustment	- Room temperature controller - Wall mounting / modern and planar design / 80 x 80 mm - Temperature sensor 5 binary and analogue inputs - TS 31.11 knx: manual adjustment of set-point temperature +/- 3°
	müller TS 37.11 knx TS 38.11 knx	Room temperature controller Room temperature controller with manual set-point temperature adjustment	- Room temperature controller - Flush-mounted fitting / fits into 55 x 55 mm switch design - Temperature sensor 5 binary and analogue inputs - TS 38.11 knx: manual adjustment of set-point temperature +/- 3°

KNX Humidity controllers

	müller GS 10.00 knx	Room temperature controller & hygrostat	- Room temperature controller and hygrostat - Wall mounting / fits into 55 x 55 mm switch design / outdoor installation - Compact housing - Temperature, humidity and atmospheric pressure sensor
	müller GS 30.11 knx GS 31.11 knx	Room temperature controller & hygrostat Room temp. controller & hygrostat with manual set-point temperature adjustment	- Room temperature controller and hygrostat - Wall mounting / modern and planar design / 80 x 80 mm - Temperature, humidity and atmospheric pressure sensor 5 binary and analogue inputs - GS 31.11 knx: manual adjustment of set-point temperature +/- 3°

KNX Air quality controllers

	müller GS 20.00 knx	VOC-air quality sensor / controller	- Air quality sensor and controller - Wall mounting / fits into 55 x 55 mm switch design / outdoor installation - VOC, temperature, humidity and atmospheric pressure sensor
	müller GS 40.01 knx GS 41.01 knx	CO ₂ -air quality sensor / controller CO ₂ -air quality sensor / controller with manual set-point temperature adjustment	- Air quality sensor and controller - Wall mounting / modern and planar design / 80 x 80 mm - CO₂, temperature, humidity and atmospheric pressure sensor - GS 41.01 knx: manual adjustment of set-point temperature +/- 3°
	müller GS 40.11 knx GS 41.11 knx	CO ₂ -air quality sensor / controller CO ₂ -air quality sensor / controller with manual set-point temperature adjustment	- Air quality sensor and controller - Wall mounting / modern and planar design / 80 x 80 mm - CO₂, temperature, humidity and atmospheric pressure sensor 5 binary and analogue inputs - GS 41.11 knx: manual adjustment of set-point temperature +/- 3°
	müller GS 47.11 knx GS 48.11 knx	CO ₂ -air quality sensor & controller CO ₂ -air quality sensor & controller with manual set-point temperature adjustment & CO ₂ /RH-monitor	- Air quality sensor and controller - Flush-mounted fitting / fits into 55 x 55 mm switch design - CO₂, temperature, humidity and atmospheric pressure sensor 5 binary and analogue inputs - GS 48.11 knx: manual adjustment of set-point temperature +/- 3°
	müller GS 70.00 knx	Particulate matter sensor & air quality controller	- Particulate matter sensor and air quality controller - VOC sensor - Temperature, humidity and atmospheric pressure sensor - Wall mounting / modern and planar design / 80 x 80 mm

KNX Outdoor sensors

	müller LS 20.00 knx	Light / brightness sensor	- Light / brightness sensor - Wall mounting (IP54) - Lighting control - Twilight switch with daily program - Daily time switch - Compact housing
	müller LS 30.00 knx	Light / brightness & temperature sensor	- Light / brightness and temperature sensor - Wall mounting (IP54) - Lighting and temperature control - Twilight switch with daily program - Daily time switch - Compact housing
	müller FU 40.00 knx	GPS sensor station with Light / brightness & temperature sensor	- GPS sensor station - Wall mounting (IP54) - Lighting and temperature control - Twilight switch with daily program - Daily & astronomic time switch - Provides time base to KNX-Bus

Further KNX-TP products

	müller EA 38.32 knx	Universal interface with 3 inputs, 2 outputs & integrated room temperature controller	- Universal interface for building automation KNX - Flush-mounted fitting 3 configurable inputs 2 binary outputs (LED / open collector) - Integrated room temperature controller - External temperature sensor available
	müller SC 98.40 knx	Digital yearly time switch 4 channels	- Yearly time switch for building automation KNX - DIN-rail mounting 70 mm 4 channels / 300 memory locations - PC-programmable - Data key function - DCF / GPS function

KNX-RF switching actuators

	paladin 683 730 rfs	Switching actuator 1 channel	- Switching actuator 1 channel - Flush-mounted fitting - Switching capacity: 16 A / 250 V - Functions: switch, timer, staircase lighting timer - KNX-RF 1.R S-Mode
	paladin 683 732 rfs	Switching actuator / shutter actuator 2 channels	- Switching actuator 2 channel / shutter actuator - Flush-mounted fitting - Switching capacity: 16 A / 250 V - Functions: shutter- / blind control - External pushbutton input - KNX-RF 1.R S-Mode

KNX-RF dimmers

	paladin 683 830 rfs	for RLC / LED loads	- RLC / LED dimmer - Flush-mounted fitting - Load 4 - 250 W - Leading- / trailing edge dimming - Additional connection for wired push-buttons - KNX-RF 1.R S-Mode
	paladin 683 831 rfs	for LED-strips	- LED-strip dimmer - Flush-mounted fitting - LED strips up to 8 A - LED strips 12 - 48 V DC - Pulse width modulation (PWM) - KNX-RF 1.R S-Mode
	paladin 683 834 rfs	for DALI ballasts	- DALI dimmer / gateway - Flush-mounted fitting 1 channel / 1 group - Up to 64 drivers can be controlled - Broadcasting communication - KNX-RF 1.R S-Mode

KNX-RF sensors and transmitters

	paladin 683 010 rfs	Pushbutton interface	- Wireless pushbutton interface - Build-in temperature sensor - Flush-mounted fitting - Input for max. 2 wired pushbuttons - Battery operated (battery lifetime approx. 8 years) - KNX-RF 1.R S-Mode
	paladin 686 312 rfs	Multi sensor	- Wireless sensor - Temperature, light and humidity - Wall mounting - Transmission of sensor values via RF - Battery operated (battery lifetime approx. 8 years) - KNX-RF 1.R S-Mode
	paladin 686 410 rfs	Door- / window contact sensor	- Door- / window contact sensor - Wall mounting - Transmission of open / close status via RF - Battery operated (battery lifetime approx. 12 years) - KNX-RF 1.R S-Mode

Accessories

	müller LA 06.10 Loudspeaker mini	- Mini Loudspeaker for flush-mounting - Nominal Impedance: 8 ohm - Suitable for: AS 25.01 knx and AS 36.03 knx
	müller LA 16.10 Loudspeaker	- Loudspeaker for flush-mounting - Nominal Impedance: 6 ohm - Suitable for: AS 25.01 knx and AS 36.03 knx
	müller TF 06 sensor / probe 4 m TF 16 sensor / probe 20 cm	- External temperature sensor - Measuring range: -15...+70°C - Cable length: 4 m / 20 cm - Suitable for: EA 36.32 knx, TS 3x.10 knx, TS 3x.11 knx, GS 3x.10 knx, GS 3x.11 knx, GS 4x.10 knx, GS 4x.11 knx
	paladin 683 520 rfs Gateway KNX RF / TP	- Gateway KNX RF / TP - Flush-mounted fitting - RF-repeater function - KNX-RF 1.R S-Mode

Mounting accessories

	Mounting plate for wall box suitable for 55 x 55 mm switch design products Order number 200.001		Mounting angle for outdoor installation IP X4 suitable for 55 x 55 mm wall mounting products Order number 200.002
	Vacuum cup suitable for 55 x 55 mm wall mounting products Order number 200.003		Back part for surface wiring suitable for 80 x 80 mm wall mounting products Order number 200.004

2025

müller
2024

www.hugo-mueller.de