



YongSung

For more than 40 years of growth & development

Proud history with the innovation &



ΠΕΡΙΕΧΟΜΕΝΑ

Control Switches

Φ16	3
Φ22	4-5
Φ25	6
Φ30	7-8

Bulletin Lamps	9
----------------------	---



<u>PILOT LAMP</u>				
MODEL		CODE	VOLTAGE - CONTACTS	
Square (S) 	Rectangular (RE) 	YSPL16-024S	- Bulb 24V 1W	R,G,Y,W
		YSPL16-024RE		R,G,Y,W



<u>ILLUMINATED PUSH BUTTON SWITCH</u>				
MODEL		CODE	VOLTAGE - CONTACTS	COLOR
Square (S) 	Rectangular (RE) 	YSPBL116-22024S	2a2b - Bulb 24V 1W	R,G,Y,W
		YSPBL116-22024RE		R,G,Y,W
		YSPBL216-22024	Latch function	R,G,Y

<u>ILLUMINATED PUSH BUTTON SWITCH</u>			
MODEL	CODE	VOLTAGE - CONTACTS	COLOR
Square (S)  	KH-516-A2-G24	2a2b - Bulb 24V AC/DC	G
	KH-516-A2-R24		R

<u>SELECTOR SWITCH</u>		
Plastic guard type	CODE	CONTACTS
Rectangular 	CSB16-SOM322-EB	1-0-2 2NO+2NC

PILOT LAMP			
MODEL	CODE	VOLTAGE - CONTACTS	COLORS
	YSAPL22-DL24	LED 24V DC	R,G,Y W
	YSAPL22-AL22	LED M/Σ 220V/24V	R,G,Y W
	YSAPL22-024	24VAC	R,G,Y,W

PUSH BUTTON			
MODEL	CODE	VOLTAGE - CONTACTS	COLORS
	YSP122-11	1NO + 1NC	R,G,Y,BL,W
	YSP122-22	2NO + 2NC	R,G,BL

SELECT LOCK PUSH BUTTON SWITCH		
MODEL	CODE	VOLTAGE - CONTACTS
	YSSP322-22R	2NO + 2NC

ILLUMINATED PUSH BUTTON SWITCH			
MODEL	CODE	VOLTAGE - CONTACTS	COLORS
	YSAPBL22-024	1NO+1NC 24V 1W	R,G,Y,W
	YSAPBL22-AL22	1NO+1NC 220V/24V	R,G,Y,W
	YSAPBL22-O06A (YSPBL22-O06)	1NO+1NC 6.3V/6,3V START	G

SELECTOR SWITCH		
MODEL	CODE	VOLTAGE - CONTACTS
	YSR22-211L	0-1 1NO+1NC
	YSR22-222L	0-1 2NO+2NC
	YSR22-311L	1-0-2 1NO+1NC

EMERGENCY PUSH BUTTON SWITCH-LOCK TURN RESET		
MODEL	CODE	VOLTAGE - CONTACTS
	CSA2X-POT11-MR	1NO + 1NC
	CSA2X-POT22-MR	2NO + 2NC

ACCESSORIES		
MODEL	CODE	DESCRIPTION
	CONTACTS	CONTACT 1NO GREEN
		CONTACT 1NC PINK
	B9AS	BULB 6.3V
	E10	BULB 6.3V
	E10	BULB 24V

PILOT LAMP			
MODEL	CODE	VOLTAGE - CONTACTS	COLORS
	YSBPL2-006A	M/Σ 6.3V/6.3V	R,G,Y,W
	YSBPL2-024A	24V 1W	R,G,W
	YSPL2-T22A	M/Σ 220V/6.3V	R,G,O,W,T
	YSBPL2-T22A	M/Σ 220V/6.3V	R,G,O,W,T
	YSBPL2-T44A	M/Σ 440V/6.3V	R,G,Y,W

PUSH BUTTON			
MODEL	CODE	VOLTAGE - CONTACTS	COLORS
	YSAP12-11	1NO + 1NC	R,G
	YSAP12-22	2NO + 2NC	G,BL
	YSAP12-44	4NO + 4NC	R

ILLUMINATED PUSH BUTTON			
MODEL	CODE	VOLTAGE - CONTACTS	COLORS
	YSNPBL2-024A	1NO + 1NC 24VAC	R,G
	YSBPBL2-024	1NO + 1NC 24VAC	R,G
	YSBPBL2-006A	M/Σ 6.3V/63V	G

PILOT LAMP			
MODEL	CODE	VOLTAGE - CONTACTS	COLORS
	YSPL3-024A	24VAC	R,G,Y,W
	YSPL3-T11A	110 / 6.3V	R,G,Y,W
	YSPL3-T22A	220 / 6.3V	R,G,Y,W
	YSPL3-T44A	440V / 6.3V	R,G,W

PUSH BUTTON			
MODEL	CODE	VOLTAGE - CONTACTS	COLORS
	YSAP13-11	1NO+1NC	R,Y,B,BL
	YSAP13-22	2NO+2NC	R,G,Y,BL

ILLUMINATED PUSH BUTTON			
MODEL	CODE	VOLTAGE - CONTACTS	COLORS
	YSNPBL3-006A	1NO + 1NC M/Σ 6,3V / 6.3V	R,G
	YSNPBL3-024A	1NO + 1NC 24VAC	R,G,Y,W
	YSNPBL3-T22A	1NO + 1NC M/Σ 220 / 6.3V	R,G,Y
	YSNPBL3-T44A	1NO + 1NC M/Σ 440 / 6.3V	R,G

SELECTOR SWITCH		
MODEL	CODE	VOLTAGE - CONTACTS
	YSAR3-211L	0-1 1NO + 1NC
	YSAR3-222L	0-1 2NO + 2NC
	YSAR3-322L	1-0-2 2NO+2NC

PUSH BUTTON SWITCH-LOCK TURN RESET		
MODEL	CODE	VOLTAGE - CONTACTS
	YSASEP334-22RA	2NO+2NC

BUZZER ø 66		
MODEL	CODE	VOLTAGE - CONTACTS
	YSEB6-24D	80X80 Frame 24VDC
	YSMB6-22A12	80X80 Frame 220VAC

Bulletin Lamps

BULLETIN SQUARE LAMP (30X30)			
MODEL	CODE	VOLTAGE - CONTACTS	COLOR
	YSBSL33-DL24 (Complete Unit)	LED 24V DC	R,G,Y
			W,BLUE
	YS3324C1-DL24 (Spare LED)	LED 24V DC	R,G,O,Y
			W,BLUE
	YS3324C1-DL11 (Spare LED)	LED 110V DC	R,G,Y,O
			BLUE
			W

LED TYPE							
Y S	B S L	3 3	—	A L	1 1	R	2 8
Yong Sung		외형치수 (Shape dimension)	사용방식 (Using method)	정격전압 (Rated voltage)	LED 색상 (Color of LED)	단의 수 (Row No.)	열의 수 (Column No.)
Bulletin Square Lamp		33 : 30×30mm 36 : 30×60mm	AL : AC LED DL : DC LED	24 : 24V(AC/DC) 48 : 48V(DC) 11 : 110V(AC/DC) 12 : AC120V/DC125V 22 : AC/DC220V 230 : AC230V 240 : AC240V	R : 적색(Red) Y : 황색(Yellow) G : 녹색(Green) O : 오렌지색(Orange) W : 백색(White) N : 청색(Navy blue)	1 : 1단(Row) 2 : 2단(Row) N : n단(Row)	1 : 1열(Column) 2 : 2열(Column) N : n열(Column)

BULLETIN RECTANGLE LAMP (30X40)			
MODEL	CODE	VOLTAGE-CONTACTS	COLOR
	YSBRL34-DL24 (Complete Unit)	LED 24V DC	R,G,Y
			W,BLUE
	YS3424C1-DL24 (Spare LED)	LED 24V DC	R,G,Y,O
			W,BLUE

LED TYPE - BRL-34							
Y S	B R L	3 4	—	A L	1 1	R	2 8
Yong Sung		외형치수 (Shape dimension)	사용방식 (Using method)	정격전압 (Rated voltage)	LED 색상 (Color of LED)	단의 수 (Row No.)	열의 수 (Column No.)
Bulletin Rectangle Lamp		30×40mm	AL : AC LED DL : DC LED	24 : 24V(AC/DC) 48 : 48V(DC) 11 : 110V(AC/DC) 12 : AC120V/DC125V 22 : AC/DC220V 230 : AC230V 240 : AC240V	R : 적색(Red) Y : 황색(Yellow) G : 녹색(Green) O : 오렌지색(Orange) W : 백색(White) N : 청색(Navy blue)	1 : 1단(Row) N : n단(Row)	1 : 1열(Column) N : n열(Column)